Safety data sheet



In accordance with 1907/2006 annex II and 1272/2008 (All references to EU regulations and directives are abbreviated into only the numeric term)



Amendment date 2024-05-13 Replaces SDS issued 2023-06-12 Revision date 2022-12-14 Version number 7.3

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Article number

UFI:

Tork Toilet Seat Cleaner Trade name

> Tork Mini Toilet Seat Cleaner 420302, 425302, 435302, 490302 OOY1-VK1W-O31S-4TV1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaning/washing agents

Not indicated Uses that are advised against

1.3. Details of the supplier of the safety data sheet

Essity Hygiene and Health AB (previously SCA Hygiene Products AB) Company

SE-40503 Göteborg

Sweden

+46 (0)31 746 00 00 Telephone

+44 1 582 677 400

E-mail info@essity.com Website www.essity.com

1.4. Emergency telephone number

Phone number for emergencies: 999 or 112. The numbers are available 24/7.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Flam. Liq. 3, H226 (See section 16)

2.2. Label elements

Hazard pictogram



Signal word Warning

Hazard statement

H226 Flammable liquid and vapour

Precautionary statements

P102 Keep out of reach of children

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P403+P235 Store in a well-ventilated place. Keep cool

P501 Dispose of contents and container to authorised waste disposal facility

Safety Data Sheet for Tork Toilet Seat Cleaner Tork Mini Toilet Seat Cleaner. United Kingdom (English) SDS-ID: 69377

2.3. Other hazards

This product does not contain any substances that are assessed to be a PBT or a vPvB

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Note that the table shows known hazards of the ingredients in pure form. These hazards are reduced or eliminated when mixed or diluted, see Section 16d.

Constituent	Classification	Concentration
ETHANOL		
CAS No: 64-17-5 EC No: 200-578-6 Index No: 603-002-00-5 REACH: 01-2119457610-43	Flam. Liq. 2, Eye Irrit. 2; H225, H319 Specific concentration limits and acute toxicity estimates (ATE): Eye Irrit. 2, H319: $C \ge 50 \%$	10 - 20 %
PROPAN-2-OL		
CAS No: 67-63-0 EC No: 200-661-7 Index No: 603-117-00-0 REACH: 01-2119457558-25	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225, H319, H336	1 - 5 %

Explanations to the classification and labelling of the ingredients are given in Section 16e. Official abbreviations are printed in normal font. Text in italics are specifications and/or complements used in the calculation of the classification of this mixture, see Section 16b.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Generally

In case of concern, or if symptoms occur, call a doctor/physician.

Upon breathing in

Fresh air and rest. If symptoms persist seek medical advice.

Upon eye contact

Rinse the eye for several minutes with lukewarm water. If irritation persists call a doctor.

Upon skin contact

Remove contaminated clothing.

Wash the skin with soap and water.

If symptoms occur, contact a physician.

Upon ingestion

First rinse the mouth thoroughly with plenty of water and SPIT OUT the rinsing water. Then drink at least half a litre of water and contact the doctor.

4.2. Most important symptoms and effects, both acute and delayed

Upon eye contact

Irritation.

Upon ingestion

Indisposition, vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguish with water mist, powder, carbon dioxide or alcoholresistant foam.

5.2. Special hazards arising from the substance or mixture

Produces fumes containing harmful gases (carbon monoxide and carbon dioxide) when burning.

Emits flammable vapours which may form an explosive mixture with air.

5.3. Advice for firefighters

Protective measures to be taken with regard to other materials at the scene of the fire.

In case of fire use proper breathing apparatus.

Wear full protective clothing.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Note the risk of ignition.

Switch off equipment which has an exposed flame, glows, or has a heat source of some other kind.

Note, risk for formation of sparks due to static electricity. Do not remove clothing in a room where spillage has occurred.

Switch off power at the main switch. Do not use the power switch in the room where the spillage has occurred.

In case of spillage in protected water, call the emergency services immediately, tel. 112 (in Europe).

Use recommended safety equipment, see section 8.

Avoid inhalation and exposure to skin and eyes.

Keep unauthorized and unprotected people at a safe distance.

6.2. Environmental precautions

Avoid release of large quantities of undiluted product to drains.

6.3. Methods and material for containment and cleaning up

Minor spillage should be wiped away or flushed away with water. Large quantities should be collected for incineration in accordance with the local regulations.

Residues after decontamination are disposed of as hazardous waste. Please contact the municipal sanitation department for more information. Show this Safety Data Sheet.

6.4. Reference to other sections

See section 8 and 13 for personal protection equipment and disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Do not eat, drink or smoke in premises where this product is handled.

Store this product separately from food items and keep it out of the reach of children and pets.

Avoid open fire, hot items, sparks or other ignition sources.

Take precautionary measures against static discharge.

Wash your hands after using the product.

Implement appropriate engineering controls if necessary, see Section 8.

Keep away from incompatible products.

Use recommended safety equipment, see section 8.

7.2. Conditions for safe storage, including any incompatibilities

The product should be stored in a manner which prevents hazards to health and the environment. Avoid exposure to humans and animals and do not discharge the product in a sensitive environment.

To be stored away from food and animal fodder and away from devices or surfaces that are in contact with those items.

Store in a well-ventilated space.

Store only in the original package.

Store in a cool and dry place (above freezing temperature and not greater than 30°C).

Do not store close to incompatible materials (see section 10.5).

7.3. Specific end use(s)

See identified uses in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters 8.1.1. National limit values ETHANOL

United Kingdom (EH40/2005)

Time-weighted-average exposure limit (TWA) 1000 ppm / 1920 mg/m³

PROPAN-2-OL

United Kingdom (EH40/2005)

Time-weighted-average exposure limit (TWA) 400 ppm / 999 mg/m³ Short term exposure limit (STEL) 500 ppm / 1250 mg/m³

DNEL ETHANOL

	Type of exposure	Route of exposure	Value
Worker	Acute Local	Inhalation	1900 mg/m ³
Consumer	Chronic Systemic	Inhalation	114 mg/m ³
Worker	Chronic Systemic	Dermal	343 mg/kg
Worker	Chronic Systemic	Inhalation	950 mg/m ³
Consumer	Acute Local	Inhalation	950 mg/m ³
Consumer	Acute Local	Dermal	950 mg/m ³
Consumer	Chronic Systemic	Oral	87 mg/kg
Consumer	Chronic Systemic	Dermal	206 mg/kg

PROPAN-2-OL

	Type of exposure	Route of exposure	Value
Consumer	Chronic Systemic	Inhalation	89 mg/m ³
Worker	Chronic Systemic	Dermal	888 mg/kg
Worker	Chronic Systemic	Inhalation	500 mg/m ³
Consumer	Chronic Systemic	Oral	26 mg/kg
Consumer	Chronic Systemic	Dermal	319 mg/kg

PNEC ETHANOL

Environmental protection target PNEC value
Fresh water 0.96 mg/l
Freshwater sediments 3.6 mg/kg
Marine water 0.79 mg/l
Marine sediments 2.9 mg/kg
Microorganisms in sewage treatment 580 mg/l
Soil (agricultural) 0.63 mg/kg
Intermittent 2.75 mg/L

PROPAN-2-OL

PNEC value Environmental protection target Fresh water 140.9 mg/l Freshwater sediments 552 mg/kg 140.9 mg/l Marine water Marine sediments 552 mg/kg Food chain 160 mg/kg dw Microorganisms in sewage treatment 2251 mg/l Soil (agricultural) 28 mg/kg Intermittent 140.9 mg/L

8.2. Exposure controls

The risks posed by the product or its constituents must be considered in the task specific risk assessment, in accordance with current working environment legislation. The risk assessment should be reviewed regularly and updated if necessary.

8.2.1. Appropriate engineering controls

The ventilation in the workplace must ensure an air quality that meets the requirements of the current working environment legislation. Local exhaust ventilation should be used to remove airborne contaminants at the source.

Maintenance and service of personal protective equipment shall be included in the works plan for internal supervision. All inspections and remedial measures shall be documented.

Emergency showers and eye-rinsing facilities must be available at the workplace.

Eye/face protection

Eye protection should be worn if there is any danger of direct exposure or splashing.

Skin protection

Wear suitable protective clothing when necessary.

It is generally not necessary to use protective gloves.

Respiratory protection

Use appropriate respiratory protective equipment in case of insufficient ventilation.

The most appropriate respiratory protective equipment should be decided in consultation with the appointed safety representative, taking into account the risk assessment for the specific task.

Based on the physical and chemical properties of the product, the following filter type(s) and/or filter combination(s) are recommended:.

– A.

8.2.3. Environmental exposure controls

Work with the product should take place in such a way that the product does not get into drains, waterways, soil and air.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

(a) Physical state liquid Form: liquid (b) Colour colourless (c) Odour like alcohol (d) Melting point/freezing point Not indicated (e) Boiling point or initial boiling point and boiling range Not indicated (f) Flammability

(g) Lower and upper explosion limit Not indicated 34.5 °C (h) Flash point (i) Auto-ignition temperature Not indicated

(j) Decomposition temperature Not indicated

When supplied, pH is: 5 - 6

Not indicated

(l) Kinematic viscosity Not indicated

(m) Solubility Solubility in water: Soluble

(n) Partition coefficient n-octanol/water (log value) Not indicated (o) Vapour pressure Not indicated (p) Density and/or relative density Not indicated (q) Relative vapour density Not indicated (r) Particle characteristics Not indicated

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Not indicated

9.2.2. Other safety characteristics

Not indicated

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

The product contains no substances which can lead to hazardous reactions at normal use.

10.2. Chemical stability

The product is stable at normal storage and handling conditions.

10.3. Possibility of hazardous reactions

May emit volatile, flammable vapours. Avoid handling close to heat or ignition sources.

10.4. Conditions to avoid

Avoid heat, sparks and open flames.

10.5. Incompatible materials

Avoid contact with oxidizers.

10.6. Hazardous decomposition products

None under normal conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Ingestion of large quantities can lead to nausea and vomiting.

Acute toxicity

The product is not classified as acutely toxic.

ETHANOL

LD50 rabbit 24h: > 20000 mg/kg Dermally

LC50 rat 4h: 124.7 mg/l Inhalation LD50 rat 10h: 38 mg/liter Inhalation LD50 rat 10h: 2000 ppm Inhalation LD50 rat 24h: 7060 mg/kg Orally

PROPAN-2-OL

LD50 rabbit 24h: 13900 mg/kg Dermally LD50 rat 24h: > 12800 mg/kg Dermally LC50 rat 4h: 72.6 mg/L Inhalation LC50 rat 4h: 64000 ppmV Inhalation LC50 rat 6h: > 25 mg/l Inhalation LC50 rat 8h: 16000 ppmV Inhalation LD50 rat 24h: 5840 mg/kg Orally

Skin corrosion/irritation

The product is not classified for skin corrosion/irritation.

Serious eye damage/irritation

The mixture is judged as a whole and is classified to be neither corrosive nor irritant to the eyes. Mild irritation may occur on prolonged or repeated exposure.

Respiratory or skin sensitisation

The product is not classified as sensitising.

Germ cell mutagenicity

The product is not classified as mutagen.

Carcinogenicity

The product is not classified as carcinogenic.

Reproductive toxicity

The product is not classified as a reproductive toxicant.

STOT-single exposure

The product is not classified for specific organ toxicity after single exposure.

STOT-repeated exposure

The product is not classified for specific organ toxicity after repeated exposure.

Aspiration hazard

The product is not classified as being toxic for aspiration.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No information is available.

11.2.2. Other information

Not indicated.

SDS-ID: 69377

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

The product is not to be labelled as a environmental hazard. However, it is not inconceivable that large emissions, or repeated small emissions, can have a harmful effect on the environment.

Avoid larger spills in soil, water and drains.

ETHANOL

LC50 Rainbow trout (Oncorhynchus mykiss) 96h: 1 - 16 g/l

LC50 fathead minnow (Pimephales promelas) 96h: > 100 mg/l

LC50 Freshwater water flea (Daphnia magna) 48h: 12340 mg/l

EC50 Algae 72 h: 275 mg/l

EC50 Freshwater water flea (Daphnia magna) 48h: 1 - 14221 mg/l

EC50 Algae (Chlorella vulgaris) 72h: 275 mg/l

PROPAN-2-OL

LC50 fathead minnow (Pimephales promelas) 96h: 9640 mg/L

LC50 fathead minnow (Pimephales promelas) 96h: 9640 - 10000 mg/l

LC50 Freshwater water flea (Daphnia magna) 48h: 2285 mg/L

EC50 Freshwater water flea (Daphnia magna) 48 h: 13299 mg/l

EC50 Freshwater water flea (Daphnia magna) 48 h: > 1000 mg/l

EC50 Algae 72 h: > 1000 mg/l

LC50 Fish 96h: 1000 mg/l

EC50 Freshwater water flea (Daphnia magna) 24h: 1 - 100 mg/l

EC50 Algae 24h: 1 - 10 mg/l NOEC Algae 72h: > 1000 mg/l

NOEC Freshwater water flea (Daphnia magna) 21d: 100 mg/l

LC50 Oryzias latipes 96h: > 100 mg/l

LC50 Freshwater water flea (Daphnia magna) 24h: 10000 mg/l

12.2. Persistence and degradability

The surfactants used in this product comply with the criteria for biodegradability under Regulation 648/2004.

12.3. Bioaccumulative potential

There is no information regarding bioaccumulation.

12.4. Mobility in soil

The product is miscible with water and is therefore variable in soil and water.

12.5. Results of PBT and vPvB assessment

This product does not contain any substances that are assessed to be a PBT or a vPvB.

12.6. Endocrine disrupting properties

No information is available.

12.7. Other adverse effects

No known effects or hazards.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste handling of the product

Discarded products must be disposed of as hazardous waste in accordance with regulations.

Not completely emptied packaging can contain remnants of dangerous substances and should therefore be handled as hazardous waste according to the above. Completely emptied packaging can be recycled.

Avoid discharge into sewers.

See directive 2008/98/EC on waste. Observe national or regional provisions on waste management.

SECTION 14: TRANSPORT INFORMATION

Where not otherwise stated the information applies to all of the UN Model Regulations, i.e. ADR (road), RID (railway), ADN (inland waterways), IMDG (sea), and ICAO (IATA) (air).

14.1. UN number or ID number

1987

14.2. UN proper shipping name

ALCOHOLS, N.O.S. (ETHANOL, PROPAN-2-OL)

14.3. Transport hazard class(es)

Class

3: Flammable liquids

Classification code (ADR/RID)

F1: Flammable liquids having a flash-point of or below 60 °C

Subsidiary risk (IMDG)

No subsidary risk according to IMDG

Labels



14.4. Packing group

Packing group III

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Tunnel restrictions

Tunnel category: D/E

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

14.8 Other transport information

Transport category: 3; Maximum total quantity per transport unit: 1000 kgs or litres (ADR 1.1.3.6)

Stowage category A (IMDG)

Emergency Schedule (EmS) for FIRE (IMDG) F-E

Emergency Schedule (EmS) for SPILLAGE (IMDG) S-D

Special provisions (ADR): 144, 601

Limited quantities (when transported according to ADR chapter 3.4): 5 L

Excepted quantities (when transported according to ADR chapter 3.5.1.2): E1.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Not indicated.

15.2. Chemical safety assessment

Assessment and chemical safety report in accordance with 1907/2006 Annex I has not yet been performed.

SECTION 16: OTHER INFORMATION

16a. Indication of where changes have been made to the previous version of the safety data sheet

Revisions of this document

Earlier versions

2023-06-12 Changes in section(s) 1.

16b. Legend to abbreviations and acronyms used in the safety data sheet

Full texts for Hazard Class and Category Code mentioned in section 3

- Flam. Liq. 2 Flammable liquids, Hazard Category 2 Flam. Liq. 2, H225 Highly flammable liquid and vapour
- Eye Irrit. 2 Serious eye damage/eye irritation, Hazard Category 2 Eye Irrit. 2, H319 Causes serious eye irritation
- STOT SE 3 Specific target organ toxicity Single exposure, Hazard Category 3, Narcosis STOT SE 3, H336 May cause drowsiness or dizziness
- Flam. Liq. 3 Flammable liquids, Hazard Category 3 Flam. Liq. 3, H226 Flammable liquid and vapour

Explanations of the abbreviations in Section 14

- ADR European Agreement concerning the International Transport of Dangerous Goods by Road
- RID Regulations concerning the International Transport of Dangerous Goods by Rail
- IMDG International Maritime Dangerous Goods Code
- ICAO International Civil Aviation Organization (ICAO, 999 University Street, Montreal, Quebec H3C 5H7, Canada)
- IATA The International Air Transport Association

Tunnel restriction code: D/E; Transport by bulk or via tank: Passage forbidden through tunnels of category D and E, Other transportation means: Passage forbidden through tunnels of category E

Transport category: 3; Maximum total quantity per transport unit: 1000 kgs or litres (ADR 1.1.3.6)

16c. Key literature references and sources for data

Sources for data

Primary data for the calculation of the hazards has preferentially been taken from the official European classification list, 1272/2008 Annex I, as updated to 2024-05-13.

Where such data was not available, alternative documentation used to establish the official classification was used, e.g. IUCLID (International Uniform Chemical Information Database). As a second alternative, information was used from reputable international chemical industries, and as a third alternative other available information was used, e.g. material safety data sheets from other suppliers or information from non-profit associations, where reliability of the source was assessed by expert opinion. If, in spite of this, reliable information could not be sourced, the hazards were assessed by expert opinions based on the known hazards of similar substances, and according to the principles in 1907/2006 and 1272/2008.

Full texts for Regulations mentioned in this Safety Data Sheet

1907/2006 REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

1272/2008 REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

648/2004 REGULATION (EC) No 648/2004 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 March 2004 on detergents

2008/98/EC DIRECTIVE 2008/98/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 19 November 2008 on waste and repealing certain Directives

16d. Methods of evaluating information referred to in 1272/2008 Article 9 which was used for the purpose of classification

Hazard calculation for this mixture has been performed as a cumulative assessment with the aid of expert assessments in accordance with 1272/2008 Annex I , where all available information which may be significant to establishing the hazards of the mixture was assessed together, and in accordance with 1907/2006 Annex XI .

16e. List of relevant hazard statements and/or precautionary statements

Full texts for hazard statements mentioned in section 3

- H225 Highly flammable liquid and vapour
- H319 Causes serious eye irritation
- H336 May cause drowsiness or dizziness

Safety Data Sheet for Tork Toilet Seat Cleaner Tork Mini Toilet Seat Cleaner. United Kingdom (English)

16f. Advice on any training appropriate for workers to ensure protection of human health and the environment Warning for misuse

This product can cause severe injuries if used improperly. Read and follow carefully the instructions in this safety sheet and other appropriate risk information. At professional use the employer is responsible for the staff being well aware of the risks.

Other relevant information

Not indicated

Editorial information



This material safety data sheet has been prepared and checked by KemRisk®, KemRisk Sweden AB, Platensgatan 8, SE-582 20 Linköping, Sweden, www.kemrisk.se