

MEDI+RANGE BOTTOM MOUNTED CABINETS WMP335/410/ WMP523



WMP335

WMP410

WMP523

Dimensions (mm)	WMP335		WMP410		WMP523	
	External	Internal	External	Internal	External	Internal
Width	595	445	695	545	727	567
Depth	684	477	684	477	837	660
Height	1956	1315	1956	1315	1940	1332
Door Opening		445		545		567
Capacity						
Capacity cu.ft/ltrs	11.8/335.5		14.5/410		18.5/523	

KEY FEATURES

- Spark free interior
- Designed and engineered to operate efficiently up to 43°C ambient
- Stainless steel exterior & aluminium interior : 335/410 models
- Stainless steel exterior & interior : 523 models
- Full length integral 'easy grab' door handle
- Self-closing, barrel locked doors
- Magnetic balloon door gaskets with 100% tight seal
- White nylon coated wire shelves
- Removable racking system with anti-tilt trayslides
- Heavy duty, non-marking, swivel castors with brakes
- Precision injected, high density 80mm polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Defrost water is vaporised using recycled heat from compressor
- High performance helium leak testing
- Air cooled condensing unit

MEDI+ CONTROLLER

- Clear digital display
- Audio and visual hi/lo temp alarm
- Audio and visual door open alarm
- Maximum and minimum temperature memory
- Auto defrost
- Air & evaporator probe
- Lockable keypad
- Condenser cleaning warning to ensure optimum performance is maintained
- Volt free alarm contacts for connecting to supervisory or BMS system
- Modbus network data connection for comprehensive monitoring of temperatures, alarms and defrost via 3rd party supervisory system
- Precise temperature control using decimal point operation

OPTIONS

- Glass door with interior LED lighting (H models only)
- Interior LED lighting for solid door (H models only)
- Punched stainless steel shelves
- Additional shelving
- Left hand door hang
- Mains failure alarm



MEDI+RANGE BOTTOM MOUNTED CABINETS WMP335/410/ WMP523

	HWMP335	LWMP335	HWMP410	HWMP523	LWMP523
Temperature (°C)	+2 / +8°C	-18 / -22°C	+2 / +8°C	+2 / +8°C	-18 / -22°C
Climate Class	Class 5 (40°C)	Class 5 (40°C)	Class 5 (40°C)	Class 5 (40°C)	Class 5 (40°C)
Power Supply	230V/50Hz/1Ph				
Fuse (Amps)	13	13	13	13	13
Defrost	Automatic Off Cycle	Automatic Off Cycle	Automatic Off Cycle	Automatic Off Electric	Automatic Electric
Noise level (dBA)	63	61	63	63	61

Fittings

White nylon coated wire shelves	4	4	4	4	4
---------------------------------	---	---	---	---	---

Electrical / Energy Data

Refrigerant	R290	R290	R290	R290	R290
Start Up (Amps)	9.5	9.5	9.5	9.5	9.5
Running (Amps)	1.7	2.47	1.75	1.67	2.59
Heat Rejection*	484	623	484	484	623

IMPORTANT NOTES:

*Heat rejection is evaporating at -10°C in 32°C Ambient
All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

