

# TRUE REFRIGERATION INTERNATIONAL

UK Tel +44 (0) 1709 888 080 • Germany Tel +49 (0) 7622 6883 0 Free Phone to U.S. 0 800 894 928 • www.truemfg.com



9/19

Model:

T-19F-HC

## **T-Series:**

Reach-In Solid Swing Door Freezer with Hydrocarbon Refrigerant



# T-19F-HC


- True's solid door reach-in's are designed with enduring quality that protects your long term investment.
- Designed using the highest quality materials and components to provide the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydro carbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).
- High capacity, factory balanced refrigeration system that maintains -10°F (-23.3°C) temperatures. Ideal for both frozen foods and ice cream.
- Stainless steel solid door and front. The very finest stainless with higher tensile strength for fewer dents and scratches.
- Adjustable, heavy duty PVC coated shelves.
- Positive seal self-closing door. Lifetime guaranteed door hinges and torsion type closure system.
- Automatic defrost system time-initiated, temperature-terminated. Saves energy consumption and provides shortest possible defrost cycle.

#### Bottom mounted units feature:

- No stoop" lower shelf.
- Storage on top of cabinet.
- Compressor performs in coolest, most grease free area of kitchen.
- Easily accessible condenser coil for cleaning.

# PLAN VIEW





PLAN VIEW

### ROUGH-IN DATA

ENERG W

D

1970

84

True | T-19F-HO

Specifications subject to change without notice. Chart dimensions rounded up to the next whole millimeter (inches rounded up to the next  $\frac{1}{2}$ ").

	Model			Cabinet Dimensions (mm)			Net Volume			24 hr/ Energy	Annual Energy Consumption	Crated Weight
Model	Туре	Doors	Shelves	W	D	Н	(litres)	EEC	EEI	(kWh)	(kWh)	(kg)
T-19F-HC	Vertical Frozen	1	4	686	623	1995	350	D	61.6	5.396	1970	120