

GEM MULTIDECKS

Williams' Gem Multidecks are one of the most popular refrigerated merchandisers for coffee shops, supermarkets, hotels, schools, universities, delicatessens, restaurants and hospitals. With the increase in 'grab & go' service, Williams' Gem Multidecks have never been in such demand! Their designer style improves your front of house, while their clever layout maximises every millimetre of retail space.

Features & Benefits

- ✓ Panoramic tempered glass sides / glass shelves for maximum all round visibility
- ✓ Adjustable shelving for maximum flexibility
- ✓ Advanced airflow technology guarantees consistent temperature control
- ✓ Between +3°C / +5°C
- ✓ Products are kept fresh and safe, while your business conforms to HACCP legislation
- ✓ Digital controller with clear temperature display
- ✓ Double wheel castors for easy positioning and levelling feet for guaranteed stability



SERIES	CODE	DIMENSIONS (mm)	SHELVES	CAP.
R - Night Blind	R125-SCN	W1250 x D615 x H1825	3	370 Ltr
R - Sliding Doors	R125-SFD	W1250 x D615 x H1825	3	370 Ltr
R - Sliding Doors	R150-SFD	W1250 x D615 x H1825	3	451 Ltr
M - Night Blind	M125-SCN	W1250 x D770 x H2080	4	607 Ltr
M - Security Shutter	M125-SCS	W1250 x D825 x H2115	4	607 Ltr



REACH IN BLAST CHILLERS

If you cook and then chill food, its temperature needs to be reduced safely from 70°C to 3°C within 90 minutes. If you are freezing cooked food, the temperature needs to go from 70°C to -18°C in no more than 240 minutes. Otherwise, you are breaking the law and worse, you are putting your customers at risk. This is because bacteria grows most aggressively between 5°C and 63°C - so the food needs to get past this 'danger zone' as quickly as possible.

Features & Benefits

- ✓ Sizes available from 10-50kg capacity to suit the size of your operation
- ✓ Designed to operate efficiently up to a 43°C ambient, exceeding Climate Class 5
- ✓ 75mm polyurethane insulation for excellent thermal efficiency
- ✓ Easy to use 1-2-3 WEB controller - 3 simple steps
- ✓ Accommodates 1/1 Gastronorm pans or shelves
- ✓ Heavy duty, non-marking swivel and brake castors
- ✓ Chiller +90°C to +3°C in 90 mins



Model	WBC10
Running Amps	4.0
W x D x H	707 x 804 x 885
Capacity	10 Kg
Electrical	13 Amp, 1 Ph



Model	WBC20
Running Amps	6.0
W x D x H	707 x 804 x 1290
Capacity	20 Kg
Electrical	13 Amp, 1 Ph



Model	WBC30
Running Amps	9.9
W x D x H	707 x 804 x 1740
Capacity	30 Kg
Electrical	16 Amp, 1 Ph



Model	WBC40
Running Amps	9.9
W x D x H	707 x 804 x 1740
Capacity	40 Kg
Electrical	16 Amp, 1 Ph



Model	WBC50
Running Amps	5.8
W x D x H	707 x 804 x 1915
Capacity	40 Kg
Electrical	16 Amp, 3 Ph